










# 160 ATJ+

## 160 ATJ +

	<b>Working height</b>	16.25 m
	<b>Platform height</b>	14.25 m
	<b>Articulation height</b>	7.00 m
	<b>Outreach</b>	8.95 m
	<b>Jib tilting</b>	+70°/-70°
	<b>Basket rotation</b>	+90°/-90°
	<b>Turret rotation</b>	350°
	<b>Capacity</b>	400 kg
	<b>Number of persons</b> (indoor/outdoor)	2/2
	<b>Basket</b> (width and length)	2.30 x 0.93 m
	<b>1. Overall width</b>	2.30 m
	<b>2. Overall length</b>	6.93 m
	<b>3. Overall height</b>	2.37 m
	<b>4. Overall length when folded</b>	4.94 m
	<b>5. Overall height when folded</b>	2.70 m
	<b>6. Inside turning circle</b>	1.32 m
	<b>7. Outside turning circle</b>	3.68 m
	<b>8. Turning Radius</b> (basket)	6.39 m
	<b>9. Ground clearance</b>	42.5 cm
	<b>10. Wheelbase</b>	2.20 m
	<b>Speed of forward movement</b>	6 kph
	<b>Working speed</b>	0.80 kph
	<b>Maximum slope accessible</b>	40%
	<b>Maximum tilt</b>	5° - 9%
	<b>Tyres</b>	18"
	<b>Driving wheels</b>	4
	<b>Steering/directional wheels</b>	4
	<b>Weight</b>	8100 Kg
	(varies according to options & standards of the country)	
	<b>Engine</b>	KUBOTA V2403-M
	<b>Power</b>	45 HP
	<b>Environmental noise</b> (LWA)	101 dB

### Standard equipment

Large Basket
Proportional levers
4 simultaneous movements
4 wheel drive
4 wheel steer
Wheels crab position
Foam filled tyres
Differential Lock
Front Axle limited slip differential
On Board Diagnostics
Hour meter
Fuel gauge with low level warning
Tool box
Protective cover with optional locking
Horn
Beacon
Audible and visual display alarm for excessive slope
Code Protected Machine Set Up
Hooks for sling loading/lifting
Electric Pump
Predisposition 230V
Dead man pedal

### Optional equipment

Oscillating Axle
Continuous Rotation
Onboard generator (3.50 kVA)
Onboard generator (5.50 kVA)
High capacity battery
230V power input with differential circuit-breaker
Predisposition compressed air
Predisposition of water
Working light
Special paint
Biodegradable oil
Warning Alarm for all movements
Warning Travel Alarm
Catalytic Converter
Spark Arrester and overrun valve
Anti Theft code
20" Wheels
Non Marking tyres
Certificate of verification
Safety harness
High capacity battery

